

SUMMIT D SERIES

ELEGANCE IN POU WATER COOLERS

FEATURES & BENEFITS

The Summit mains connected point of use system is designed for those areas that command the look of style and elegance. Perfectly suited for domestic kitchens, executive offices or to compliment any reception area, the brightly polished stainless steel cabinet ensures a prestigious look and easy cleaning and maintenance.

The water storage tanks are almost double the reservoirs of most water coolers on the market. This allows you to fill a jug for the meeting table with out depleting the water supply for the next user.

The faucets are durable polypropylene self closing taps. Child resistant taps are available as an option or as standard on hot/cold systems.

Hot & cold tanks are both made of hygienic stainless steel

Double float valve maintains water level in reservoir.

Easily converts to a bottled water unit by removing the float valve and inserting a "Dry Guard" non spill kit (Optional)

REFRIGERATION SYSTEM

Ozone friendly R134a refrigerant. Refrigerant charge 28.4g

ELECTRICAL

240 Volts, 50Hz single phase. A 1.8 metre house cable and 3 pin plug is supplied.

ITEM		SPECIFICATIONS
POWER RATING		Single phase
		(220-240V 50Hz)
		(100-115V 60Hz)
STANDARD CURRENT		H&C: 6.2A, C&C: 1.2A
POWER CONSUMPTION	Cold	74W
	Hot	450W
COLD	Compressor	Single phase motor (TS24 LATG)
	Refrigerant	R134a
	Temp range	6°C ± 3°C (43 °F ± 37.4 °F)
	Temp control	Thermostat (ON - 0°C to 8.9°C ± 1.5°C) (OFF -17.8°C ± 1.5°C)
	Capacity	3.5L (0.9 gal)
HOT	Heater	Band heater
	Temp range	75-92°C (167-197.6°F)
	Safety device	Bimetal (Manual reset 95°C OFF)
	Temp control	Bimetal 84-92 °C (183.2-197.6°F)
	Capacity	4.5L(1.2 gal)
REFRIGERANT CHARGE		28.4g (1.0 oz)
NOISE (SOUND POWER LEVEL)		38dB(A)
PRODUCT WEIGHT		H&C: 17.5kg (38.6 lb), C&C: 16.6kg (36.7 lb)
PRODUCT BOXED WEIGHT		H&C: 20.4kg (45.0 lb), C&C: 19.5kg (43.0 lb)
PRODUCT DIMENSIONS		305(W) X 312(D) X 980(H)mm
		12.0"(W) X 12.3"(D) X 38.6"(H)
PRODUCT BOXED DIMENSIONS		375(W) X 400(D) X 1055(H)mm
		14.8"(W) X 15.8 "(D) X 41.5"(H)
LOADING QUANTITY		20' Container: 168 Units
		40' Container: 348 Units
CERTIFICATIONS		C-UL-US, CE, CB, CCC, SASO

As part of Waterworks Australia's policy of continuous improvement, we reserve the right to alter specifications at anytime without notice.

Distributed by...



Waterworks Australia Pty Ltd ABN 51 064 901 239
 48 Neumann Road Capalaba Queensland 4157
 Phone (07) 3390 3777 • Fax (07) 3390 1766
 Email sales@water-works.com.au • www.water-works.com.au